

## Digital Clamp Meters

**Access difficult testing areas with the 1 $\frac{3}{16}$ " (30 mm) jaw opening**

Reliably detect and measure the power quality running to your equipment to quickly find hidden issues. These meters feature durable, double-molded plastic housing and jaw.

### Features

- ◆ Reliable measurements, guaranteed! Precalibrated to NIST-traceable standards
- ◆ Large backlit display provides easy-to-read measurements
- ◆ Autorange feature automatically selects optimal measuring range
- ◆ Low-battery indicator alert for when it's time for a fresh battery

### 400 A AC Clamp Meters (20250-55, -56)

- ◆ Diode testing, continuity check with a buzzer sound at 50  $\Omega$ , and a measurement rate of 2 readings per second
- ◆ Built-in noncontact AC voltage detector
- ◆ CAT III-1000 V safety rating
- ◆ Improved measurement ease with data Hold function
- ◆ Model 20250-56 also measures DC current and capacitance, and features a peak Hold function that captures the peak AC current or voltage reading

### 1000 A AC Clamp Meters (20250-57, -58)

- ◆ Improve accuracy with True RMS check for load current and AC voltage, as well as continuity of contacts, fuses, circuits, and switches
- ◆ See power variations on analog bar graph display
- ◆ CAT III-600 V safety rating
- ◆ Model 20250-58 also features DC current measurement and True RMS for more accurate current readings



20250-55



20250-58

**Precalibrated &  
Ready to Use!**

## Applications

- ◆ Electrical
- ◆ Industrial
- ◆ Laboratory
- ◆ HVAC
- ◆ R & D

## Includes

Test leads, temperature probe (models 20250-55, -56, and -58), carrying case, 9 V battery, and NIST-traceable calibration report supplied by InnoCal.

**\*Calibration certificate provided by InnoCal®**, an ISO17025 accredited laboratory (A2LA certificate 1746.01) offering a broad range of NIST-traceable calibration services.

**For recalibration, call 1-866-466-6225 or e-mail [info@innocal.com](mailto:info@innocal.com).** Their full complement of services can be viewed at [www.innocal.com](http://www.innocal.com).



Description	400 A AC clamp meter	400 A AC/DC clamp meter	1000 A AC clamp meter	1000 A AC/DC clamp meter
Catalog number	MW-20250-55	MW-20250-56	MW-20250-57	MW-20250-58
AC current	400 A	400 A (True RMS)	1000 A	1000 A (True RMS)
DC current	—	400 A	—	1000 A
AC voltage (True RMS)	600 V	600 V	750 V	750 V
DC voltage	600 V	600 V	1000 V	800 V
Resistance	40 MΩ	40 MΩ	60 MΩ	60 MΩ
Capacitance	—	4 mF	4000 μF	100 μF
Frequency	10 kHz	100 kHz	10 MHz	10 MHz
Duty cycle	Yes	—	Yes	Yes
Continuity	Yes, audible	Yes, audible	Yes, audible	Yes, audible
Diode	Yes	Yes	Yes	Yes
Temperature (type K thermocouple)	-4 to 1400°F (-20 to 760°C)		—	-4 to 1832°F (-20 to 1000°C)
Display	4000-count LCD		6000-count LCD, with backlight and analog bar graph	
Dimensions (W x H x D)	7¾" x 2¾" x 1⅞" (19.7 x 7 x 4 cm)		8⅞" x 3⅞" x 1⅞" (22.6 x 8 x 4.3 cm)	
Power	One 9 V battery (included)		One 9 V battery (included)	



### USA

#### Cole-Parmer

Toll-free: 1-800-323-4340  
Phone: 1-847-549-7600  
[ColeParmer.com](http://ColeParmer.com)

#### For Calibration, InnoCal

Toll-free: 1-866-466-6225  
[InnoCalSolutions.com](http://InnoCalSolutions.com)

#### IN CANADA

Toll-free: 1-800-363-5900  
Phone: 1-514-355-6100  
[ColeParmer.ca](http://ColeParmer.ca)

#### IN CHINA

Phone: +86-21-5109-9909  
[ColeParmer.com.cn](http://ColeParmer.com.cn)

#### IN GERMANY

Phone: +49 (0) 9377 9203-0  
[ColeParmer.de](http://ColeParmer.de)

#### IN INDIA

Phone: 1-800-266-1244  
[ColeParmer.in](http://ColeParmer.in)

#### IN THE UNITED KINGDOM

Phone: 020-8574-7556  
[ColeParmer.co.uk](http://ColeParmer.co.uk)

#### INTERNATIONAL CUSTOMERS

Call 1-847-549-7600  
[ColeParmer.com/dealers](http://ColeParmer.com/dealers)



[sales@novatech-usa.com](mailto:sales@novatech-usa.com)  
[www.novatech-usa.com](http://www.novatech-usa.com)

Tel: (866) 433-6682 Fax: (866) 433-6684  
Tel: (281) 359-8538 Fax: (281) 359-0084