



**Precalibrated &
Ready to Use!**

Stick-Style Water-Resistant Infrared Thermometers

**Unique ergonomic stick-style design
fits comfortably in your hand**

These innovative handheld infrared (IR) thermometers deliver precise measurements, quickly and easily, without physically touching the object. Simply aim, push the button, and read—reliable measurements couldn't be any easier!

Both models feature

- ♦ Water- and dust-resistant IP54 rating
- ♦ Single targeting laser
- ♦ Fixed emissivity
- ♦ Automatic data Hold
- ♦ Backlit display
- ♦ User-selectable readout in °F or °C
- ♦ Auto power-off extends battery life

General-purpose model 20250-09 features

- ♦ Reliable measurements, guaranteed! Precalibrated to NIST-traceable standards.*
- ♦ Distance-to-sight ratio of 8:1
- ♦ Temperature range: 0 to 575°F (–18 to 302°C)
- ♦ $\pm 2\%$ basic accuracy

Foodservice model 35625-15 features

- ♦ Distance-to-sight ratio of 4:1 is ideal for the food industry
- ♦ Temperature range: –31 to 575°F (–35 to 302°C)
- ♦ $\pm 1\%$ basic accuracy

Applications

- ♦ Agricultural
- ♦ Educational
- ♦ Food processing
- ♦ HVAC
- ♦ Industrial
- ♦ Laboratory
- ♦ R & D
- ♦ Preventive maintenance

Includes

One 9 V battery. Model 20250-09 also includes a NIST-traceable certificate with data and uncertainties.

*Calibration certificate provided by InnoCal®, an ISO17025 accredited laboratory (A2LA certificate 1746.01) offering a broad range of NIST-traceable calibration services. For recalibration, call 866-466-6225 or e-mail info@innocalsolutions.com. Their full complement of services can be viewed at www.innocalsolutions.com.



Catalog number	WD-20250-09	WD-35625-15 [†]
Distance-to-sight ratio	8:1	4:1
Temperature range	0 to 575°F (-18 to 302°C)	-31 to 575°F (-35 to 302°C)
Resolution	0.1°	0.1°
Accuracy	±3.6°F (2°C) or ±2% of reading	From 39° to 150°F (4 to 65°C): ±2°F (1°C) Below 39°F (4°C): ±3.6°F (2°C) Above 150°F (65°C): ±[1% + 2°F (1°C) of reading]
Response time	Less than 500 ms	Less than 500 ms
Emissivity	Fixed at 0.95	Fixed at 0.97
Laser pointer	Single Class 2 (II) laser	Single Class 2 (II) laser
Size (L x W x H)	7" x 1¾" x 1½" (17.8 x 4.4 x 3.8 cm)	7" x 1¾" x 1½" (17.8 x 4.4 x 3.8 cm)

[†]Note: Model 35625-15 is not supplied with a NIST-traceable certificate but can be calibrated for an additional charge at any time.



sales@novatech-usa.com
www.novatech-usa.com

Tel: (866) 433-6682

Fax: (866) 433-6684

Tel: (281) 359-8538

Fax: (281) 359-0084