# Traceable® Platinum High-Accuracy Freezer Thermometers

## Extreme accuracy— Platinum wide-range



Cat. No. 6411

#### View the time and date MIN/MAX readings occurred

- Triple display shows current, MIN/MAX temperatures
- Time/date stamp key shows exact time and date for all MIN/MAX readings
- Smart-Alarm<sup>™</sup>—a visual/audible alarm that continues to alarm even if unit returns to non-alarm conditions

#### **Features:**

- Unique history program displays MIN/MAX temperatures for previous 24 hours (for each hour); and previous 7-days (for each day) or previous 31 days (for each day)
- °C/°F switchable

- Sealed GRAS bottle is insulated from rapid temperature changes when door is opened; GRAS—liquid generally recognized as safe by US Food and Drug Administration
- Alarm is settable in 0.1° increments and signals when temperature rises above/ falls below set points

#### Traceable to NIST for accuracy

An individually-numbered Traceable® Certificate is provided which assures accuracy from an ISO/IEC 17025:2005 (1750.01) calibration laboratory accredited by A2LA. It indicates traceability to standards provided by NIST (National Institute of Standards and Technology).

Cat. No. 6408 Traceable® Platinum High Accuracy Thermometer, 1 Bottle Probe +FREE Traceable® Atomic Clock Cat. No. 6409 Traceable® Platinum High Accuracy Thermometer, 1 Bullet™ Probe +FREE Traceable® Atomic Clock Cat. No. 6410 Traceable® Platinum High Accuracy Thermometer, 1 SS Probe +FREE Traceable® Atomic Clock Cat. No. 6411 Traceable® Platinum High Accuracy Thermometer, 1 Bullet™ Probe +FREE Traceable® Atomic Clock





6409/6411

### Product Specifications

**6408/6409** 

**Range:** -58.00 to 158.00°F

(-50.00 to 70.00°C)

**►** 6410

**Range:** -148.00 to 199.99°F

(-100.00 to 199.99°C)

**►** 6411

**Range:** -148.00 to 158.00°F

(-100.00 to 70.00°C)

► Resolution: 0.01°

► Accuracy: ±0.1°C

► Size: 2<sup>3</sup>/<sub>4</sub> x 4<sup>1</sup>/<sub>4</sub> x <sup>3</sup>/<sub>4</sub>"

► Weight: 5 ounces

► Supplied: batteries, platinum

RTD stainless-steel bottle probe, cable, magnetic strips, Velcro® tape, bench stand, Traceable® Certificate