

Lovibond® Water Testing Tintometer® Group



ET830

Precise flocculation tests for cost-effective water and wastewater treatment.



- Flocculation tests according to ASTM D2035-19
- Time-controlled or manual speed change
- Portable design
- High vessel compatibility

Part Number: 2419110

The Floc Tester series impresses with its standard-compliant tests, flexible application and user-friendly design.

Compliance with standards

Performs flocculation tests in accordance with ASTM D2035-19

High vessel compatibility

Suitable for beakers from 500 mL to 1500 mL (1500 mL: ET830 complete, ET840 and ET850 at half the stirring positions)

Two-step testing mode

Time-controlled or manual switching between two adjustable speeds for reproducible tests

Flexible configurations

Four (ET830 & ET840) or six (ET850) stirring positions with continuously adjustable stirrer height

Durable

Corrosion-resistant stainless steel stirrers

Optimal readability

Large, illuminated display

Simple & universal operation

Intuitive, language-independent operating concept

Precise speed control

Digital adjustment from 20 to 250 rpm

Versatile timer options

Programmable from 1 to 240 minutes or continuous operation

High mobility

Sturdy transport handles, 12 V DC car adapter (ET830)

Optimal visibility

The ET840 & ET850 models offer flexible lighting from behind or below. The mobile Floc Tester ET830 provides lighting from above.

Industry

Chemical Industry | Food and Beverage Industry | Industries Others | Oil and Gas | Pharmaceutical Industry

ET830

The Lovibond® Flocc Tester enables reproducible laboratory simulations of real treatment conditions and allows operators to determine the correct type of flocculant and the optimum dosage before large-scale use. This ensures safe, economical and sustainable water treatment.

Technical Data

Voltage	100 - 240 V
Frequency	50/60 Hz
Output Voltage Power Supply	15 VDC
Fuse	5x20 mm, F3.15AL250 V
Max. Power	50 W
Display	LCD backlit
Operation	Membrane keys
Portability	Portable
Timer	0 - 240 minutes and ∞
Motor	DC Gear Motor with Encoder
Stirring Places	4 (portable)
Stirring Speed Control	20 - 250 revolutions per minute
Resolution	5 rmp
Precision	± 1 rmp

Rod and Stirrer Material	Stainless Steel
Compliance	CE
Protection Class	Power Supply: Class II, Device: Class III
Dimensions	10.04 x 16.85 x 9.96"

Delivery Scope

- With 6 stirring units
- Regulator for rpm from 10-300 rpm
- Display stirring rate and time
- Switch for rear panel illumination
- Instruction manual
- Warranty information

Title	Part Number
Measuring beaker, glass 1000 ml	419165
Measuring beaker, PP 1000 ml	419166
Measuring beaker, glass 1500 mL	419167
Bag for transport Flocc Tester ET830	419174

Tintometer GmbH

Lovibond® Water Testing
Schleefstraße 8-12
44287 Dortmund
Tel.: +49 (0)231/94510-0
sales@lovibond.com
www.lovibond.com
Germany

The Tintometer Limited

Lovibond House
Sun Rise Way
Amesbury, SP4 7GR
Tel.: +44 (0)1980 664800
sales@lovibond.uk
www.lovibond.com
UK

Tintometer China

9F, SOHO II C. No.9 Guanghualu,
Chaoyang District,
Beijing, 100020
Customer Care Tel.: +86 (021) 69910081
Tel.: +86 10 85251111 Ext. 330
Fax: +86 10 85251001
chinaoffice@tintometer.com
www.lovibond.com
China

Lovibond Tintometer Sdn Bhd

Unit B-3-12, BBT One Boulevard,
Lebuh Batu Nilam 2, Bdr Bkt Tinggi,
41200, Klang, Selangor,
Tel.: +60 (0)3 3325 2285/6
Fax: +60 (0)3 3325 2287
lovibond.asia@tintometer.com
www.lovibond.com
Malaysia

Tintometer Brazil

Caixa Postal: 271
CEP: 13201-970
Jundiaí – SP
Tel.: +55 (11) 3230-6410
sales@lovibond.us
www.lovibond.com.br
Brazil

Tintometer Inc.

6456 Parkland Drive
Sarasota, FL 34243
Tel: 941.756.6410
Fax: 941.727.9654
sales@lovibond.us
www.lovibond.us
USA

Tintometer India Pvt. Ltd.

Door No: 7-2-C-14, 2nd, 3rd & 4th Floor
Sanathnagar Industrial Estate,
Hyderabad, 500018
Telangana
Tel: +91 (0) 40 23883300
Toll Free: 1 800 599 3891/ 3892
indiaoffice@lovibond.in
www.lovibondwater.in
India

Tintometer Spain

Postbox: 24047
08080 Barcelona
Tel.: +34 661 606 770
sales@tintometer.es
www.lovibond.com
Spain