

Tygon® E-3603 Tubing

Non-oxidizing and Non-Contaminating

E-3603 Tubing

Use the clear and flexible Tygon E-3603 tubing for various general laboratory applications. This non-oxidizing and non-contaminating tubing offers excellent chemical resistance to virtually all organic chemicals used in the laboratory. High tolerances and lot-to-lot consistency ensure reproducible results.

Tubing slips over fittings and grips tight for a secure fit, making laboratory setup quick and simple. Abrasion and flex-fatigue resistant tubing provides superior life span.



CERTIFICATION

Cole-Parmer will provide a certificate of compliance FREE at your request where applicable.

APPLICATIONS

- General-purpose, laboratory, and single-use applications

FEATURES/BENEFITS

- Free technical application support available to assist with tubing selection
- Smooth, polished inner wall prevents buildups
- Excellent lot-to-lot consistency for reproducible results
- Great flex fatigue resistance
- BPA and phthalate free

USA	+1.800.323.4340
	+1.847.549.7600
Canada	+1.800.363.5900
China	86.21.5109.9909
France	+33 (0) 1486 37800

Germany	+49 (0) 9377 92030
India	+1.800.266.1244
Italy	+39 (0) 1313 89513
UK	+44 (0) 1480.272279
All others	+1.847.549.7600

Specification and Ordering Table

Dimensions: in. (mm)			Max pressure: PSI (bar)	Item number	Roll length (ft)
Tubing ID	Tubing OD	Wall			
1/32"	3/32"	0.03125 (0.8)	70 (4.8)	50106-20	50
1/16"	1/8"	0.03125 (0.8)	36 (2.5)	50106-21	50
1/16"	3/16"	0.0625 (1.6)	70 (4.8)	50106-22	50
3/32"	5/32"	0.03125 (0.8)	25 (1.7)	50106-23	50
3/32"	7/32"	0.0625 (1.6)	46 (3.2)	50106-24	50
1/8"	3/16"	0.03125 (0.8)	20 (1.4)	50106-25	50
1/8"	1/4"	0.0625 (1.6)	36 (2.5)	50106-26	50
5/32"	7/32"	0.03125 (0.8)	17 (1.2)	50106-27	50
3/16"	5/16"	0.0625 (1.6)	25 (1.7)	50106-28	50
3/16"	3/8"	0.09375 (2.4)	36 (2.5)	50106-29	50
1/4"	3/8"	0.0625 (1.6)	20 (1.4)	50106-30	50
1/4"	7/16"	0.09375 (2.4)	28 (1.9)	50106-31	50
1/4"	1/2"	0.125 (3.2)	36 (2.5)	50106-32	50
5/16"	7/16"	0.0625 (1.6)	17 (1.2)	50106-33	50
5/16"	1/2"	0.09375 (2.4)	23 (1.6)	50106-34	50
5/16"	9/16"	0.125 (3.2)	30 (2)	50106-35	50
3/8"	1/2"	0.0625 (1.6)	15 (1)	50106-36	50
3/8"	9/16"	0.09375 (2.4)	20 (1.4)	50106-37	50
3/8"	5/8"	0.125 (3.2)	25 (1.7)	50106-38	50
7/16"	9/16"	0.0625 (1.6)	13 (0.9)	50106-39	50
1/2"	5/8"	0.0625 (1.6)	12 (0.8)	50106-40	50
1/2"	11/16"	0.09375 (2.4)	15 (1)	50106-41	50
1/2"	3/4"	0.125 (3.2)	20 (1.4)	50106-42	50
1/2"	13/16"	0.15625 (4)	25 (1.7)	50106-43	50
5/8"	13/16"	0.09375 (2.4)	13 (0.9)	50106-44	50
5/8"	7/8"	0.125 (3.2)	17 (1.2)	50106-45	50
3/4"	1"	0.125 (3.2)	15 (1)	50106-46	50
3/4"	1-1/8"	0.1875 (4.8)	20 (1.4)	50106-47	50
1"	1-1/4"	0.125 (3.2)	12 (0.8)	50106-48	50
1"	1-1/2"	0.25 (6.4)	20 (1.4)	50106-49	50



sales@novatech-usa.com
www.novatech-usa.com

Tel: (866) 433-6682 Fax: (866) 433-6684
Tel: (281) 359-8538 Fax: (281) 359-0084

Cole-Parmer®
an antylia scientific company