

Tygon® F-4040-A Tubing

Fuel and Lubricant

A-60-G Tubing

Use the high-performance Tygon F-4040-A tubing for transferring fuels and industrial lubricants. Specially formulated tubing resists swelling and hardening caused by many hydrocarbon-based fluids that can lead to tubing failure.

Low permeation rating makes this tubing perfect for transferring gasoline, kerosene, heating oils, and glycol-based coolants. Highly flexible translucent yellow tubing provides quick identification, easy monitoring of the flow, and fast installation, even in tight places.



CERTIFICATION

Cole-Parmer will provide a certificate of compliance FREE at your request where applicable.

APPLICATIONS

- General-purpose, laboratory, and single-use applications

FEATURES/BENEFITS

- Free technical application support available to assist with tubing selection
- Resists swelling and hardening caused by hydrocarbon-based fluids
- Low extractables help maintain fluid integrity
- Flexible and easy to install
- Translucent yellow tubing provides quick identification
- Ozone and UV resistant

USA	+1.800.323.4340
	+1.847.549.7600
Canada	+1.800.363.5900
China	86.21.5109.9909
France	+33 (0) 1486 37800

Germany	+49 (0) 9377 92030
India	+1.800.266.1244
Italy	+39 (0) 1313 89513
UK	+44 (0) 1480.272279
All others	+1.847.549.7600

Specification and Ordering Table

Dimensions: in. (mm)			Max pressure: PSI (bar)	Item number	Roll length (ft)
Tubing ID	Tubing OD	Wall			
3/16"	5/16"	0.0625 (1.55)	35 (2.4)	50105-93	50
1/8"	1/4"	0.0625 (1.6)	50 (3.4)	50105-92	50
1/4"	3/8"	0.0625 (1.55)	50 (3.4)	50105-94	50
5/16"	7/16"	0.0625 (1.6)	25 (1.7)	50105-95	50
3/32"	3/16"	0.046875 (1.2)	50 (3.4)	50105-91	50
3/4"	1"	0.125 (3.2)	20 (1.4)	50105-98	50
3/8"	1/2"	0.0625 (1.6)	20 (1.4)	50105-96	50
1/2"	5/8"	0.0625 (1.6)	15 (1)	50105-97	50



sales@novatech-usa.com

www.novatech-usa.com

Tel: (866) 433-6682

Fax: (866) 433-6684

Tel: (281) 359-8538

Fax: (281) 359-0084

Cole-Parmer®
an antylia scientific company