

Features

- \cdot Capable of reaching up to 12,000 revolutions per minute.
- · It has 4 rotors and adapters for tubes of different capacities.
- · Adjustable speed.
- · Compact and easy to transport.

Applications

- · Clinical laboratories
- · Cell biology

- · Blood banks
- · Molecular biology
- $\cdot \, {\sf Biochemistry}$

► Accessories included

- · Rotor # 1, 6 x 0.2 / 0.5 / 1.5 / 2ml
- · Rotor # 4, 12 x 30mm / 40mm hematocrit
- · Three-phase cable

- Rotor # 2, 2 x 8 x 0.2ml
- · 6 adapters for 0.5ml
- · Rotor # 3, 4 x 3ml / 5ml
- · 6 adapters for 0.2ml

TE	СН	NI	CAL	. D	ATA

Model PRO-12K
Speed range 1000-12,000 RPM (Variable range depending on the rotor).

Manual.

Maximum RFC 6,900 g (Variable force depending on the rotor).

Rotor capacity 4 x 3ml/5ml.

6 x 0.2ml/0.5ml/1.5ml/2ml.

12 hematocrit capillaries 30mm/40mm.

16 x 0.2ml.

Weight 1100 g / 2.2 lb.

Dimensions 180 x 150 x 130 mm / 7.0" x 5.9" x 5.1". **Power supply** 110/240V, 50/60 Hz AC adapter.

Warranty l year

